

ATH Hytron Lift 2.40 HB

Product Images



- **Modern design – pioneering technology – impressive appearance**
- Electro-hydraulic 2-post lift with space-saving “triangular columns”, each of the two independent columns is wirelessly controlled by an industrial radio, without disturbing rigid top connection.
- **ATH Hytron concept**
 - 1) ASC control (ATH Safety Control) to synchronize two independent columns, each equipped with a hydraulic power unit
 - 2) Speed and pressure control
 - 3) ATH plunger cylinder system, very strong and long-lasting
 - 4) Service-friendly hydraulic ATH-Hytron concept, all components in one place for easy maintenance
- Columns with variable width, no connection required
- Two control units for flexible use on both columns
- Energy set (230V / compressed air / USB) on both columns
- Safety Control: Electromagnetic MicroAnts tracked safety Latches that unlock automatically by lifting and lowering, as well as for setting down the load
- Multipurpose pick-up with 3-stages lifting arms and double telescopic lifting pads. Optionally with telescopic double jointed arm in the back.
- “Plug and play” factory assembly, set up, plug in, fill with oil, done
- Improve the quality of any workshop with a high-grade and attractive design, by covering all components

Additional Information

Color	Anthrazitgrau
Rated load capacity	4.000 kg
Lifting height max.	2.000 mm
Drive-through width	2.310 – 2.500 mm
Overall width	3.050 – 3.240 mm
Overall height	3.220 mm
Support arms parts	3
Driving power	2 x 2,2 KW
Lifting/Lowering time	ca. 32 s
Software Plattform	ATH HeartBeat
Power supply voltage	3x 400V / C16A
Concrete strength	min. C20/25 4.000 x 2.000 x 180 mm

